Product Data Sheet

Austrotherm Resolution® Floor (Boden)

High-performance thermal insulation made of rigid phenolic foam (resol) with a closed-cell structure. Ideally suited for floor insulation. Extremely slim build-up heights are possible in floor assemblies.

- Super slim: space-saving insulation solution
- More room height thanks to an extremely low build-up
- Excellent fire behaviour

Application:	Areas subject to compressive loads (under screed, under underfloor heating)
Delivery form:	Board dimensions: 1000 x 500 mm Available thicknesses: 25 – 300 mm Edge profile: straight edge (GK)
Product type:	Rigid phenolic foam (PF), in accordance with ÖNORM EN 13166
Facing:	None
Designation code:	EN 13166 - T(1) - DS(N) - DS(70,90) - DS(-20,-) - CS(10)120 - CV

Technical data

Thermal conductivity	**0.022 W/mK**
Compressive strength	**120 kPa**
Shear modulus	**> 250 kPa**
Shear strength	**> 30 kPa**
Density	**approx. 35 kg/m³**
Closed-cell content	**≥ 90 %**
Water vapour diffusion resistance factor	**20**
Reaction to fire, EN 13501-1	**C-s1, d0**

Note:
Austrotherm Resolution® is resistant to short-term contact with petrol and to most diluted acids, alkalis and mineral oils. In case of long-term contact of Austrotherm Resolution® with adhesive or adhesive mortar, one with a maximum pH value of 12 must be used.

Austrotherm Resolution® contains no chlorofluorocarbons (CFCs), HCFCs or HFCs, nor HBCD, and is free of chlorine and chlorides.

Development and Application Technology
Revised: 10/2024

Our application-technology recommendations, given verbally and in writing to support the buyer/processor on the basis of our experience and in line with the current state of science and practice, are non-binding and do not establish any contractual legal relationship or any ancillary obligations under the purchase contract. They do not relieve the buyer from the obligation to check our products themselves for suitability for the intended purpose.